




# AQUOS 24 H<sub>2</sub>O

## PELLET IDRO H<sub>2</sub>O - Water-heating pellet stoves



Nominal power	kW	24,8
Reduced power	kW	6
Nominal water useful power	kW	22,7
Reduced water useful power	kW	5
Nominal efficiency	%	91,6
Reduced efficiency	%	95,1
Heating volume (min-max)	m <sup>3</sup>	144 - 595
Nominal CO at 13% O <sub>2</sub>	%	0,008
Reduced CO at 13% O <sub>2</sub>	%	0,024
Nominal dust content at 13% O <sub>2</sub>	mg/Nm <sup>3</sup>	7,2
Boiler capacity (H <sub>2</sub> O)	l	25
Hopper capacity	kg	70
Combustible		Pellet ø6
Hourly consumption (min-max)	kg/h	1,2 - 5,2
Autonomy (min-max)	h	13,5 - 58,3
Ignition electrical absorption (max)	W	430
Operating electrical absorption (max)	W	120
Supply and frequency	V - Hz	230 - 50
Chimney flue depression	Pa	12,2
Exhaust diameter	mm	100
Combustion air inlet diameter	mm	80
Mass of smoke (min-max)	g/sec	17,1
Exhaust fumes temperature (max)	°C	116,5
Net weight	kg	230 - 245
Gross weight	kg	240 - 255
Exhaust fumes	see	A
Hole combustion air inlet	see	B
Ducting outlet	see	-



Art. 15A B-VG 2015  
BImSchV 2015  
Regensburg  
München  
Stuttgart  
Aachen



### MATCH

7015049	NEUTRAL STRUCTURE	EAN 8033123616744
6915023	Ivory majolica	EAN 8033123616522
6915024	Red majolica	EAN 8033123616539
6915021	Ivory steel	EAN 8033123616508
6915022	Red steel	EAN 8033123616515

### PLUS



Complete kit heating + domestic water



Hydraulic kit included



Cast iron burning pot



Overheating protection



Burnproof handle



Ventilation



Wi-Fi kit (optional)



Daily weekly programming



Connection to the external thermostat



Air temperature sensor




Water temperature sensor



Back exhaust


### STOVE PACKING



L (cm)	H (cm)	P (cm)
80	142	80


VOLUME (m <sup>3</sup> )
0,91

### LINING PACKING



	L (cm)	H (cm)	P (cm)
steel	46	8	96
majolica	50	30	47

### STOCKING



### TRANSPORT

