## **HYDROBRONPI-60E**












































- Heating power: 22kw
- Power transferred to water (kW): 17kw
- Efficiency (%): 76%
- Consumption (kg/h): 6.5kg/h
- Heating capacity (m3): 550m3
  Hopper capacity (I): 45I
- Ceramic inside
- Manufactured in cast-iron and sheet
- Weight (kg): 108kg
- Smoke exit tube diameter (mm): 200mm
- Clean glass system
- Useful oven measures: 536 X 274 X 390mm
- Working pressure (bar): 1.5bar
- Maximum logs size (cm): 54cm
- Underfloor heating (m2):170
- Nº radiator elements: 122
- Compatible accesories not included: F-503; KIT-1; KIT-2; VAL-01; VAL-02









## **HYDROBRONPI-70E**












































- Heating power: 24kw
- Power transferred to water (kW): 19kw
- Efficiency (%): 76%Consumption (kg/h): 7.1kg/h
- Heating capacity (m3): 600m3
- Tank capacity (I): 70I
- Metallic interior
- Manufactured in cast-iron and sheet
- Weight (kg): 154kg
- Smoke exit tube diameter (mm): 200mm
- Clean glass system
- Useful oven measures: 636 X 314 X 459mm
- Working pressure (bar): 1.5bar
- Maximum logs size (cm): 64cm
- Underfloor heating (m2): 190
- No radiator elements: 136
- Compatible accesories not included: F-503; KIT-1; KIT-2; VAL-1; VAL-3









## **HYDROBRONPI-80E**



































F-503 KIT-1 KIT-2 VAL-01 VAL-03

## **Features**

- Heating power: 27kw
- Power transferred to water (kW): 22.5kw
- Efficiency (%): 76%
- Consumption (kg/h): 7.8kg/h
- Heating capacity (m3): 675m3
   Tank capacity (I): 90I
- Metallic interior
- Manufactured in cast-iron and sheet
- Weight (kg): 221kgSmoke exit tube diameter (mm): 200mm
- Clean glass system
- Useful oven measures: 727 X 359 X 503mm
- Working pressure (bar): 1.5bar
- Maximum logs size (cm): 72cm
- Compatible accesories not included: F-503; KIT-1; KIT-2; VAL-01; VAL-03



