




KOOK 67 4.0



Free standing wood cookers



Nominal power	kW	6,2
Reduced power	kW	-
Introduced thermal power (max)	kW	9,5
Nominal water useful power	kW	-
Reduced water useful power	kW	-
Nominal efficiency	%	84,1
Reduced efficiency	%	-
Heating volume (min-max)	m ³	149
Nominal CO at 13% O ₂	%	0,097
Reduced CO at 13% O ₂	%	-
Emissions CO (13% O ₂) (min-max)	mg/Nm ³	1209
Emissions OGC (13% O ₂) (min-max)	mg/Nm ³	69
Emissions NOX (13% O ₂) (min-max)	mg/Nm ³	78
Dust content at 13% O ₂ (min- max)	mg/Nm ³	29,8
Boiler capacity (H ₂ O)	l	-
Hopper capacity	kg	-
Combustible		Legna
Hourly consumption (min-max)	kg/h	1,7
Autonomy (min-max)	h	-
Ignition electrical absorption (max)	W	-
Operating electrical absorption (max)	W	50
Supply and frequency	V - Hz	230 - 50
Chimney flue depression	Pa	12
Exhaust diameter	mm	140
Combustion air inlet diameter	mm	-
Mass of smoke (min-max)	g/sec	7,3
Exhaust fumes temperature (max)	°C	168
Net weight	kg	*
Gross weight	kg	*
Exhaust fumes	see	A
Hole combustion air inlet	see	B
Ducting outlet	see	-
Ducting capability up to	m	-



Art. 15A B-VG 2015
BImSchV 2016
Regensburg
München
Stuttgart
Aachen



MATCH

71190010	NEUTRAL STRUCTURE with cast iron Top	EAN 8053859010883
71190011	NEUTRAL STRUCTURE with cast iron Top with ventilation + light kit	EAN 8053859010890
6919001	Ivory majolica	EAN 8053859011163
6919002	Red majolica	EAN 8053859011170
6919003	Ivory steel	EAN 8053859011187
6919005	White steel	EAN 8053859011200
6919004	Red steel	EAN 8053859011194

PLUS



Cooking



Upper and back exhaust



Refractory stone inner with 2nd combustion air




OPTIONAL
Ventilation + light kit



View on the oven


STOVE PACKING



L (cm)	H (cm)	P (cm)
77	100,5	79


VOLUME (m ³)	0,61
--------------------------	------

LINING PACKING



	L (cm)	H (cm)	P (cm)
steel	60	13,5	80
mayolica	73	22	34

STOCKING



TRANSPORT

